



29-1/2" undermount single-bowl farmhouse kitchen

sink

K-6486

#### **Features**

- 30" (762 mm) minimum base cabinet width
- Single bowl
- 9" (229 mm) depth provides generous workspace
- Short 6-11/16" (170 mm) apron allows sink to be used in new or existing standard cabinetry
- Self-Trimming® apron overlaps cabinet face for easy installation and beautiful results
- Bowl slopes toward drain to minimize water pooling
- Offset drain increases workspace in the sink and storage space underneath



KOHLER® enameled cast iron

### Installation

- Cutout templates included
- Undermount

### **Recommended Products/Accessories**

K-6638 Sink racks for 30" Whitehaven kitchen sink K-8801 Sink drain and strainer with tailpiece K-8799 Sink drain and strainer basket K-23726 Drain treatment K-23725 Cast iron cleaner

## **Optional Products/Accessories**

K-11352 Disposal Flange with Stopper K-9000 P-Trap



## Codes/Standards

ASME A112.19.1/CSA B45.2

# KOHLER® Enameled Cast Iron Kitchen and Bathroom Sink Lifetime Limited Warranty

See website for detailed warranty information.

#### **Available Colors/Finishes**

Color tiles intended for reference only.

Color	Code	Description
	0	White
	FF	Sea Salt™
	96	Biscuit
	NY	Dune
	95	Ice™ Grey
	58	Thunder™ Grey
	7	Black Black™
Les	DGB	Indigo Blue








29-1/2" undermount single-bowl farmhouse kitchen sink

K-6486



#### **Technical Information**

All product dimensions are nominal.

Bowl configuration: Single Installation: Undermount Min. base cabinet 30" (762 mm)

width:

Bowl area (Only): Length: 24-3/4" (629 mm)

Width: 18-1/16" (459 mm) Bowl depth: 9" (229 mm)

Drain hole: 3-5/8" (92 mm)

Template: 1156909-7, required, included

1211543-7, required, included

#### **Notes**

Install this product according to the installation instructions.

NOTICE: Countertop manufacturer or cutter must use the current product template available at www.kohler.com, or by calling 1-800-4KOHLER. Kohler Co. is not responsible for cutout errors when the incorrect cutout template is used.

IMPORTANT! The distance from the top edge of the cabinet to the top of the cabinet door must be at least 6-7/8" (175 mm) to install this

sink.

